



Typ	Montageabstand M(4) / M(7)	Nabenlänge M(21)/M(26)	Nabdurchmesser M(22) / M(27)	Abstand Nabe zu Rohr M(30)	Schraubabstand M(37) (Rahrende)	Befestigungs - Gewinde M(38)	Teilkreis M(39)
GX-1	5	18	56	2	11	M6	44/2
GX-2	5	20	85	4	10	M8	68/2
GX-4	5	25	97	4	12	M8	80/3
GX-8	5	30	117	4	14	M10	100/3
GX-16	5	35	150	6	18	M12	125/3
GX-25	5	40	170	6	20	M14	140/3

Typ	S1018	S1220	S1424	S1524	S1624	S1830	S1930	S2030	S2238	S2438	S2538	S2842	S3042	S3250	S3550	S3858	S4058
d-Welle	10	12	14	15	16	18	19	20	22	24	25	28	30	32	35	38	40
D-Nabe	18	20	24	24	24	30	30	30	38	38	38	42	42	50	50	58	58
SW	22	22	27	27	27	36	36	36	46	46	46	50	50	55	55	65	65

Gelenkwellentext : Ausführung, Baugröße, Spannsatz1,Spannsatz2, Gesamtlänge M(3)

Beispiel : GX-1-S1424-S1424-840