

Example: Alpha 20-B-225-SSS-M-2505-1000-1660-FB-2EMS-0

Product _____

Size (version*) _____

Drive _____

S = Spindle

Guide system _____

S = Rail guide

Model _____

S = Standard

Type of drive _____

M = Single nut (ball screw)

MM = Double nut (ball screw)

(TR = Trapezoidal screw - optional)

Drive specifications _____

Diameter and pitch (ball screw)

(Diameter x pitch (trapezoidal screw) - optional)

Stroke _____

Total length _____

Cover _____

FB = Bellows

Accessories _____

EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted

EO2 / EO10 = Inductive limit switch NC with 2 m / 10 m cable fitted

ES2 / ES10 = Inductive limit switch NO with 2 m / 10 m cable fitted

NS / RM = Sliding block 1 .. 11 / Rhomb nut 4 .. 6 (see Table on **page A6**)

Special design _____

0 = Standard

1 = Special (add specification description)

Additional accessories (separate position)

MGK = Motor mounting and coupling (according to dimension sheet)

URT = Deflection belt drive (according to dimension sheet)

Further drives available on request:

MK or TK (= single nut made of plastic), KK (= double nut made of plastic)

* currently only version „B“ available