

Example:

Beta 80-ZRS-32 AT5-E-220-1000-1420-AK-AZ1-1

Product	
Size (version*)	
Drive	
Z = Toothed belt drive	
0 = Without drive	
A = Powered carriage	
Guide system	
R = Roller guide	
S = Rail guide	
G = Sliding guide	
0 = Without guide	
Model	
S = Standard	
Drive specifications	
Width and type of toothed belt	
Stroke per revolution	
Stroke	
Total length	
Cover	
AK = Cover band (Note: Total length is greater for Beta 80 and Beta 100)	

Accessories

- BL = Mounting bracket
- EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted
- EO2 / EO10 = Inductive limit switch NC with 2 m / 10 m cable fitted
- ES2 / ES10 = Inductive limit switch NO with 2 m / 10 m cable fitted
- NS ① .. ⑭ = Sliding block ① .. ⑭ (See Table on **page B50**)
- AZ1 = Drive shaft short, mounting side **C**
- AZ1-GX = Drive shaft long without feather key groove, mounting side **C**
- AZ2 = Drive shaft short, mounting side **D**
- AZ2-GX = Drive shaft long without feather key groove, mounting side **D**
- AZ6 = Drive shaft short, mounting side **C** and **D**
- AZ6-GX/C = Drive shaft short, mounting side **D** and
Drive shaft long without feather key groove, mounting side **C**
- AZ6-GX/D = Drive shaft short, mounting side **C** and
Drive shaft long without feather key groove, mounting side **D**
Further arrangements for drive shaft, see **page Z1**
- AZx-S = Drive shaft special (x=1 side **C**, x=2 side **D**, x=6 side **C** und **D**)

Special design

- 0 = Standard
- 1 = Special (add specification description)

Further accessories (separate position)

- MGK = Motor mounting and coupling (according to dimension sheet)
- URT = Deflection belt drive (according to dimension sheet)

* e.g. Beta 80-ZSS or Beta 80-C-ZSS