

Example: **Delta** 145-C-ZSS-50 AT5-E-110-1000-1340-AK-AZ1-1

Product	
Unit size (version*)	
Drive	
Z = Toothed belt drive 0 = Without drive	
Guide system	
S = Rail guide R = Roller guide	
Model	
S = Standard ; A = Alternative (profile unmachined)	
Drive specifications	
Width and type of toothed belt	
Stroke per revolution	
Stroke	
Total length	
Cover	
AK = Cover band	
Accessories	
BL = Mounting bracket	
EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted	
EO2 / EO10 = Inductive limit switch NC with 2m / 10m cable fitted	
ES2 / ES10 = Inductive limit switch NO with 2m / 10m cable fitted	
NS 1 .. 21 = Sliding block ① .. ⑩ (see Table on page D16)	
AZ1 = Drive shaft short, mounting side C	
AZ2 = Drive shaft short, mounting side D	
AZ6 = Drive shaft long, mounting side C and D	
AZX = Integrated drive shaft (standard, not Delta 110-C and 145-C)	
Further arrangements for drive shaft, see page Z1	
Special design	
0 = Standard	
1 = Special (add specification description)	

Further accessories (separate position)

MGK = Motor mounting and coupling (according to dimension sheet)

URT = Deflection belt drive (according to dimension sheet)

* e.g. Delta 240-ZSS or Delta 240-C-ZSS