

Example: Delta 145-C-SSS-M-2010-1000-1360-2SA-2ES2-6BL2-0

Product

Unit size (version*)

Drive

S = Spindle

O = Without drive

Guide system

S = Rail guide

R = Roller guide

Model

S = Standard ; A = Alternative (profile unmachined)

Type of drive

M = Single nut (ball screw)

MM = Double nut (ball screw)

(TR = Trapezoidal screw - optional)

Drive specifications

Diameter and pitch (ball screw)

(Diameter x pitch (trapezoidal screw) - optional)

Stroke

Total length

Spindle support (SA)

(quantity)

Accessories

EO2 / EO10 = Inductive limit switch NC with 2m / 10m cable fitted

ES2 / ES10 = Inductive limit switch NO with 2m / 10m cable fitted

EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted

BL = Mounting bracket

NS / RM = Sliding block 1 .. 21 / Rhomb nut 2 .. 6 (see Table on **page D16**)

Special design

0 = Standard

1 = Special (add specification description)

Further accessories (separate position)

MGK = Motor mounting and coupling (according to dimension sheet)

URT = Deflection belt drive (according to dimension sheet)

For mounting of limit switches and lubrication points, see **page Z1**

Cover band comes as standard for screw drive

Further drives available on request:

MK or TK (= single nut made of plastic), KK (= double nut made of plastic)

* e.g. Delta 240-SSS or Delta 240-C-SSS