

Example:

Delta 145-C-ZSS-50 AT5-E-110-1000-1340-AK-AZ1-8RM4-1

Product

Unit size (version*)

Drive

Z = Toothed belt drive

O = Without drive

Guide system

S = Rail guide

R = Roller guide

Model

S = Standard ; A = Alternative (profile unmachined)

Drive specifications

Width and type of toothed belt

Stroke per revolution

Stroke

Total length

Cover

AK = Cover band

Accessories

AZ1 = Drive shaft short, mounting side **C**

AZ2 = Drive shaft short, mounting side **D**

AZ6 = Drive shaft long, mounting side **C** and **D**

AZX = Integrated drive shaft (standard, not Delta 110-C and 145-C)

Further arrangements for drive shaft, see **page Z1**

EO2 / EO10 = Inductive limit switch NC with 2 m / 10 m cable fitted

ES2 / ES10 = Inductive limit switch NO with 2 m / 10 m cable fitted

EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted

BL = Mounting bracket

NS / RM = Sliding block 1 .. 21 / Rhomb nut 2 .. 6 (see Table on **page D16**)

Special design

0 = Standard

1 = Special (add specification description)

Further accessories (separate position)

MGK = Motor mounting and coupling (according to dimension sheet)

URT = Deflection belt drive (according to dimension sheet)

* e.g. Delta 240-ZSS or Delta 240-C-ZSS