

Example: **Gamma 160-ZSS-50 ATL10-240-1000-1620-AZ1-1**

Product	_____
Unit size	_____
Drive	_____
Z = Toothed belt drive	
0 = Without drive	
A = Powered carriage	
Guide system	_____
S = Rail guide	
0 = Without guide	
Model	_____
S = Standard (Horizontal)	
SD = Standard double (Horizontal)	
H = Lifting axis (Vertical)	
Drive specifications	_____
Width and type of toothed belt	
Stroke per revolution	_____
Stroke	_____
Total length	_____

Accessories

- EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted
 - EO2 / EO10 = Inductive limit switch NC with 2m / 10m cable fitted
 - ES2 / ES10 = Inductive limit switch NO with 2m / 10m cable fitted
 - NS ⑤ , ⑥ , ⑰ = Sliding block ⑤ , ⑥ , ⑰ (see Table on **page G27**)
 - AZ1 = Drive shaft short, mounting side **C**
 - AZ2 = Drive shaft short, mounting side **D**
 - AZ6 = Drive shaft long, mounting side **C** and **D**
- Further arrangements for drive shaft, see **page Z1**

Special design

- 0 = Standard
- 1 = Special (add specification description)

Further accessories (separate position)

- MGK = Motor mounting and coupling (according to dimension sheet)