

**Example:**

**Gamma** 160-ZSS-50 ATL10-240-1000-1620-AZ1-8NS6-1

**Product**

**Unit size**

**Drive**

Z = Toothed belt drive

0 = Without drive

A = Powered carriage

**Guide system**

S = Rail guide

0 = Without guide

**Model**

S = Standard (Horizontal)

SD = Standard double (Horizontal)

H = Lifting axis (Vertical)

**Drive specifications**

Width and type of toothed belt

**Stroke per revolution**

**Stroke**

**Total length**

**Accessories**

AZ1 = Drive shaft short, mounting side **C**

AZ2 = Drive shaft short, mounting side **D**

AZ6 = Drive shaft long, mounting side **C** and **D**

Further arrangements for drive shaft, see **page Z1**

EO2 / EO10 = Inductive limit switch NC with 2 m / 10 m cable fitted

ES2 / ES10 = Inductive limit switch NO with 2 m / 10 m cable fitted

EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted

NS = Sliding block 5 .. 17 (see Table on **page G27**)

**Special design**

0 = Standard

1 = Special (add specification description)

**Further accessories** (separate position)

MGK = Motor mounting and coupling (according to dimension sheet)