

Example: **Sigma** 120-ZRS-40 AT10-200-1000-1440-AZ1-1

Product	
Size	
Drive	
Z = Toothed belt drive	
0 = Without drive	
A = Powered carriage	
Guide system	
R = Roller guide	
Model	
ZRS = Standard (Horizontal)	
ZRSD = Standard double (Horizontal)	
ARH = Lifting axis (Vertikal)	
ARS = Standard (Horizontal)	
Drive specifications	
Width of toothed belt and tooth pitch	
Stroke per revolution	
Stroke	
Total length	
Accessories	
BL = Mounting bracket	
EMS / EMB = Mechanical limit switch (S = Siemens, B = Balluff) fitted	
EO2 / EO10 = Inductive limit switch with 2 m/10 m cabel fitted	
ES2 / ES10 = Inductive limit switch with 2 m/10 m cabel fitted	
NS ② .. ⑩ = Sliding block ② .. ⑩ (See Table on page S17)	
AZ1 = Drive shaft short, mounting side C	
AZ2 = Drive shaft short, mounting side D	
AZ6 = Drive shaft long, mounting side C and D	
Further arrangements for drive shaft, see page Z1	
Special design	
0 = Standard	
1 = Special (add specification description)	

Further accessories (separate position)

MGK = Motor mounting and coupling (according to dimension sheet)